

Lexan Radiance 3" and 4.5" LED Overhead Light

Features

- Available in 3" or 4.5", spring or screw mount options
- Warm white 3000K or cool white 4000K light output
- ITC interior RV LED lighting is standardized on one LED for light color consistency among fixtures
- Power saving LED technology
- **MacAdam Ellipse** color control technology; color difference between fixtures guaranteed to be undetectable to the human eye
- Excellent thermal management for a long 50,000 hour estimated LED life as compared to a 2,000 hour estimated life of a halogen bulb
- Lexan lens provides the appearance of frosted glass while offering maximum light output and a soft diffused light

Product Details

	69231PC 3"	69240PC 4.5"
Housing	PC 2807	
Lens	High Diffusion Lexan	
Cutout	2.25"	3.5"
Voltage	12V	
Wattage	2.6 W	3.8 W
Amp Draw [@ 12V]	.21 A	.32 A
Lumen Output	160 LM	250 LM
LED Color Temperature	3000K or 4000K	



Specification Guide

Sample Part #: 69240PCNS-15-3KE

Base Part #
 Mounting Option
 # of LEDs
 Color Temperature

Lexan Radiance Light Specification			
Base Part #	Mounting Option	# of LEDs	Color Temp.
3" Diameter Version			
69231PC	NS - Screw Mount * Leave blank for spring mount	9 - 9 LEDs	3KE - 3000K 4KE - 4000K
4.5" Diameter Version			
69240PC	NS - Screw Mount * Leave blank for spring mount	15 - 15 LEDs	3KE - 3000K 4KE - 4000K



Product Dimensions

