

4.5" Radiance™ Overhead LED Light

Features

- Available in 12, 15, and 21 LED options depending on your lighting needs.
- Pleasing warm white light output.
- Power saving LED Technology.
- **MacAdam Ellipse** color control technology: color difference between fixtures guaranteed to be undetectable to the human eye.
- Excellent thermal management for long 50,000 hour estimated LED Life as compared to a 2,000 estimated life of a halogen bulb.
- Light output comparable to ITC's 20W halogen.
- Patented twist lock holds glass into place for easy replacement and stylish appearance.
- Spring clip or screw mount - no visible fasteners.
- Mercury, Lead & UV free.
- FCC compliant.

Product Details

	12 LED	15 LED	21 LED
Housing	CRS, powder coated white		
Lens	Frosted Glass		
Diameter	4.5"		
Cutout Diameter	3.5"		
Required Clearance Depth	1.5" min		
Wattage	4.3 W	5.8 W	8.3 W
Voltage:	12V DC		
Amp Draw: [@ 13.6V DC]	0.32 A	0.43 A	0.61 A
Integral Switch	No		
LED Color	3000K ±175K		
Light Output	200 LM	260 LM	340 LM
Wire Size	18 AWG		

Part Numbers

69240-12-3KE	12 LED Spring Mount
69240NS-12-3KE	12 LED Screw Mount
69240-15-3KE	15 LED Spring Mount
69240NS-15-3KE	15 LED Screw Mount
69240-21-3KE	21 LED Spring Mount
69240NS-21-3KE	21 LED Screw Mount



Product Dimensions

